



Amigo® Lift-It

SPECIFICATIONS MODEL 990000

PLACEMENT SURFACES

- Cars, Vans or Trucks w/Class II or III Receiver Hitch
- Vans and Trucks Must Have Swing-Away or Hatch-Type Doors
- Fold-Down Tailgates Not Compatible

SPEED AND POWER

- 12V Gear Motor
- Stand-Alone DC Power Source/Back-up Battery
(Comes With Each Lift-It Purchase)

DIMENSIONS

- 22.5-31.0 Inches (57.2-78.7 cm) Arm Extension
- 38-44.5 Inches (96.5-113.03 cm) Vertical Adjustment

COMPONENTS

- Boom and Post Assembly – 18 lbs (8.19 kg)
- Swivel Bar – 10 lbs (4.55 kg)
- Mounting Bracket (Consists of Hitch Bracket and Swivel Position Tube) – 13 lbs (5.91 kg)
- Stand-Alone DC Power Source – 12 lbs (5.46 kg)

PROVIDES

- No Permanent Installation Required
- Fully Transferable From Vehicle to Vehicle*
- No Unsightly Hardware or “Hardwiring”
- Fully Charged Power Source = Estimated 20-23 Full Up/Down Cycles
- Compact Size/Adjusts Easily
- Lift-Arm Fits Seat Posts 1.5 to 2 inches (3.81 cm to 5.08 cm) in diameter
- Maximum 200 lb (90.91 kg) Lifting Capacity
- Amigo 3-year Limited Warranty
- Power Source Manufacturer’s Warranty (Universal Battery 888-826-4223)

* **Requires Class II (1.25 in / 3.2 cm square tube) or Class III (2 in / 5.1 cm square tube) Receiver Hitch.**

Minimum Opening Width = 56" (142.2 cm)

Minimum Opening Height = 38" (96.5 cm)

(Measured from the Center of the Hitch Square up to the Lowest Point of Opening)

AMIGO MOBILITY INTERNATIONAL, INC.

6693 Dixie Highway • Bridgeport, MI 48722-9725
800 248-9131 • www.myamigo.com